



Features

- Excellent sound absorption, 1.38 NRC
- High performance, cost-effective
- 2 grommets per baffle
- Class A fire-rated, per ASTM E-84
- Made in the USA

Applications

- Warehouse
- Industrial Facilities
- Gymnasium
- Multi-purpose Rooms
- Dance Halls
- Cafeterias

Description

Ambience Polywrap Baffles enhance the quality of sound in a room. Ambience Polywrap Baffles are suspended from the ceiling to reduce sound reflections from hard surfaces such as walls, floor, and ceiling. Eliminate the echo to enhance the listening experience in a large facility.

Ambience Polywrap Baffles are easy to install. Includes 2 brass grommets along one of the four foot sides. Optional spacing or additional grommets available.

Easy to maintain. Clean with a damp cloth.

Options

- White or Black

Performance

Sound Absorption (frequencies in Hz)

Frequency (Hz)	125	250	500	1000	2000	4000	NRC
Polywrap Baffle, 1-1/2" x 2' x 4"	0.25	0.80	1.35	1.75	1.60	1.00	1.38

Test Method: ASTM C423-90a and C423-81

	125	250	500	1000	2000	4000	NRC
Sound Absorption in Sabins per Baffle	2.1	6.5	10.7	14.1	12.7	8.1	11.0

Physical Properties

	Weight (Lbs)	Thickness (nominal)	Density (pcf)	Burn Tests
Polywrap Baffle	2.0	1.5 in	1.6	Flame Spread: 8 Smoke Density: 0
Test Method				ASTM E-84, Class A