



Features

- Class A fire-rated, per ASTM E-84, self-extinguishing, California TB #117
- NRC up to 0.93
- Finished surface or wall panel core
- Lightweight, 2 pounds per cubic foot
- Affordable
- Made in the USA

Applications

- Music Rooms
- Home Theaters
- Recording Studios
- Gymnasiums
- Auditoriums
- Offices
- Arenas
- Stadiums
- Computer Rooms
- Pro Audio
- Manufacturing Plants
- Machine Enclosures
- Classrooms
- Residential

Description

Material:	Convoluted acoustic foam
Pattern:	Pyramids
Features:	up to 0.93 NRC
Thickness and Size:	1", 2", and 3"
Density:	2 pounds per cubic foot (pcf)
Color:	Charcoal
Flame & Smoke Index	Flame spread 25, Smoke spread 250
Maintenance	Clean dust with soft brush accessory using low setting on vacuum cleaner. High suction may tear foam. Test on small area.

Performance

Pyramids Sound Absorption (octave frequencies in Hz)

Product	Nominal Size*	Density (pcf)	125	250	500	1000	2000	4000	NRC
1" Pyramids	12"x12", 24"x24"	2	0.12	0.24	0.20	0.55	0.95	1.02	0.50
2" Pyramids	12"x12", 24"x24"	2	0.14	0.29	0.60	0.89	1.04	1.03	0.71
3" Pyramids	12"x12", 24"x24"	2	0.25	0.49	0.75	0.99	1.05	1.07	0.80
4" Pyramids	12"x12", 24"x24"	2	0.30	0.51	0.99	1.13	1.09	1.12	0.93